

WOW III

THE NEW GENERATION OF WOW MODULE SERIES



200 lm/w

WOW III Module, the new generation of WOW Series Module, bring this market-favored products to the next level, greatly enhancing the efficiency to 200lm/w while retaining the beloved design.

SPECIFICATIONS

- Designed for medium to large channel letters
- 3"-12" Depth Min
- 7+5 Year Warranty
- 12VDC
- L80 rating of 50,000 hours
- UV Resistant; UV and IR Protected
- High Efficiency

SPECIFICATIONS CHART

SPECIFICATION	DETAILS
Product Options	White (7500K / 6300K / 5000K / 2700K)
Input Voltage	12VDC
Beam Angle	172°
Power Consumption (watts)	1.2w/mod
LED / Module	3
Modules / Foot	1.3/ft. fully stretched
Lumen / Module	243.6lm (7500K), 233.86lm (6300K), 228.9lm (5000K), 221.68lm (2700K)
Lumen / Foot	316.68lm (7500K), 304.02lm (6300K), 279.57lm (5000K), 288.18lm (2700K)
Protection Grade	IP67
Operating Temp	-40° ~ +60°C / -40° ~ +140°F
Storage Temp	-40° ~ -70°C / -40° ~ +158°F
Cascade	25 mods single-ended power feed, 50 mods double-ended power feed
Packaging	25pcs/chain, 50pcs/bag, 10 bags/outer carton

MODULES POPULATION GUIDE

CHANNEL LETTER DEPTH (IN)	MULTIPLE ROWS (ROWS SPACING)	CLEARANCE	MODS PER FT
3"	4"	2"	1.5
4"	7"	3"	1.5
5"-6"	10"	5"	1.3
7"-10"	12"	6"	1.3

DIMENSIONS

