

WOW II MAX

CHANNEL LETTER SOLUTION

Perfect for any size of channel letters and cabinets, the WOW II MAX feature a 170-degree lens, enabling effective usage in as little as a 2" depth channel letters.


SPECIFICATIONS

- Designed for medium to large channel letters
- 3M double-face tape and mechanical mounting options
- 3"-12" Depth Min
- 7+5 Year Warranty
- 12VDC; 24VDC
- L80 rating of 50,000 hours
- UV Resistant; UV and IR Protected
- High Efficiency

OPTIONS

MODEL	VOLTAGE	COLOR TEMP	LUMENS
WOW II MAX 7500k	12V	7500K	160.2 lm/mod (200.25 lm/W)
WOW II MAX 6300k	12V	6300K	155.39 lm/mod (194.24 lm/W)
WOW II MAX 4200K	12V	4200K	152.19 lm/mod (190.24 lm/W)
WOW II MAX 2700K	12V	2700K	145.78 lm/mod (182.23 lm/W)
WOW II MAX 7500k	24V	7500K	163.2 lm/mod (204 lm/W)
WOW II MAX 6300k	24V	6300K	158.3 lm/mod (197.88 lm/W)
WOW II MAX 4200K	24V	4200K	155.04 lm/mod (193.8 lm/W)
WOW II MAX 2700K	24V	2700K	148.51 lm/mod (185.64 lm/W)

DIMENSIONS



UL®
E344189

G2G
LIGHTING

200 lm/w

SPECIFICATIONS CHART

SPECIFICATION	DETAILS
Product Options	White (7500K/6300K/4200K/2700K)
Input Voltage	12VDC/ 24VDC
Beam Angle	172°
Power consumption (watts)	0.8W/mod, 1.2W/ft
LED / module	2
Modules / foot	1.5 Mods/ft. fully stretched
Protection Grade	IP67
Operating Temp	-40° ~ +60°C / -40° ~ +140°F
Storage Temp	-40° ~ -70°C / -40° ~ +158°F
Cascade	12VDC 25 mods single-ended power feed, 50 mods double-ended power feed
	24VDC 40 mods single-ended power feed, 80 mods double-ended power feed
Packaging	12VDC 35pcs/chain, 70pcs/bag, 10 bags/outer carton
	24VDC 40pcs/chain, 120pcs/bag, 7 bags/outer carton

MODULES POPULATION GUIDE

CHANNEL LETTER DEPTH (IN)	MULTIPLE ROWS (ROWS SPACING)	CLEARANCE	MODS PER FT
3"	4"	2"	2
4"	6"	3"	1.5
5" – 6"	10"	5"	1.5
7" – 10"	12"	5"	1.5

